



sashmate[®]

top hung rolling bar

Please use this step by step guide along side the Instruction Manuals, Aide memoire and demonstration films already provided.

All of the above can be found online at
<https://www.glazesafe.com//use-sashmate/>

All Sashmate components should be inspected before and after use. Any damage should be reported to the Competent Person in charge of safety in your organisation.

In all cases safety remains the responsibility of the engineer using the Sashmate Tools.

Standard safety precautions such as, but not limited to, edge protection, safety cordons below the work area, necessary labour to carry the sash into and back out of the building must be considered.

The Sashmate Tools should not be used in adverse weather conditions.

The Sashmate Tools should only ever be used by experienced engineers who have been sufficiently trained on the Sashmate products.



Remove the sledges from the horizontal arms.



Install the Sashmate Top Hung in the usual way.



Install the second side in the usual way.



Feed the sledge through the square tube on the rolling bar with the square tube facing upwards and the round tube below it.



Install the sledges into the horizontal arms. This can be done one at a time if easier. Make sure the rolling bar is below the sledges as shown here.



Tighten the screws mid way along the horizontal arms.



Release the horizontal arm screw and raise the horizontal arm until the sledge meets the bottom of the sash. Repeat on the second side and tighten screws.



Pull in the sledges to meet the sash and tighten the screws mid way along the horizontal arms.



Place a sheet over the outer frame/ transom bar. Remove the hinge fixings in the normal way.



Support the sash. Glass suckers may help to carry the sash in to the building.



Turn the sash side ways on to the rolling bar and the outer frame/ transom bar.



Roll the sash into the building until the sash is manageable to carry in.



Roll the sash out and then lift into position.



Open the hinges into position, raise the top pins and re fit the fixings in the usual way.



Release the screws mid way along the horizontal arm and extend the sledges outwards, clear of the sash.



Release the horizontal arm screws and allow the horizontal arms to drop.



Release the sledge screws and carry the sledges and rolling bar into the building. This can be done one at a time if easier.



Remove the Sashmate Top Hung in the usual way.